



62-021 Sarbinowo  
ul. Długa 12  
tel.+48 61 897 36 03/04/32  
e-mail: [biuro@norson.pl](mailto:biuro@norson.pl)  
[norson@norson.pl](mailto:norson@norson.pl)

## DECLARATION OF PERFORMANCE No. 09/2025

1. The name and trade name of the construction product:  
**RK pipe flange adaptors, RR pipe couplings, RKPE adaptors with brass insert, RRPE couplings with brass insert, RKF expansion joints.**
2. Type designation of a construction product:  
**RK PN 10/16 flange adaptors, catalog number 1-141 000...**  
**RR PN 10/16 pipe couplings, catalog number 1-142 000...**  
**RKPE PN 10/16, flange adaptors with brass insert, catalog number 1-143...**  
**RRPE PN 10/16, couplings with brass insert catalog number 1-145...**  
**RKF PN 10/16 compensating connectors, catalog numbers 1-144...**
3. Intended use or uses of a construction product:  
**used for connecting and repairing iron, steel, PE, PVC, cement and asbestos pipes in various combinations.**
4. Name and address of the manufacturer's premises and place of production of the product:  
**Norson Sp. z o.o. Sp. K.**  
**Sarbinowo, ul. Długa 12**  
**62-021 Paczkowo**
5. Where appropriate, the name and contact address of the authorized representative whose mandate covers the tasks specified in art. 12 p. 2:  
**not applicable.**
6. System or systems for assessment and verification of constancy of performance of a construction product as defined in the Annex to the Regulation:  
**system 4.**
7. National technical specification:  
  
7a. Polish Product standard:  
a) PN-EN 1074-1:2002,  
b) PN-EN 14525:2023-04,  
c) PN-EN 1092-1 :2018-08,  
d) PN-EN 12842:2012  
e) PN-EN 1563:2018-10

The name of the accredited certification body, accreditation number and national certificate number or the name of the accredited laboratory: N/A

7b. National technical evaluation: N/A


8.Declared performance:

| Essential characteristics     | Useful properties   | Technical Specifications     |
|-------------------------------|---|------------------------------|
| - tightness                   | fulfills  | PN-EN 14525:2023-04          |
| - maximum working pressure    | 1.0 MPa or 1.6 MPa<br>(according to the manufacturer's designation) |                              |
| - external protective cover   | epoxy paint with a thickness of<br>min. 250µm                       | manufacturer's specification |
| - working temperature         | from 0°C - 70°C   |                              |
| - diameter range              | according to the catalog  |                              |
| - flange drilling             | fulfills  | PN-EN 1092-1 :2018-08        |
| - connection dimensions       | fulfills  | PN-EN 12842:2012             |
| - body, ring                  | EN-GJS-500-7  | PN-EN 1563:2018-10           |
| - protection ring (RKPE,RRPE) | brass MO59  | manufacturer's specification |
| - sealing                     | EPDM  |                              |

9. The performance of the product specified above is in accordance with all declared performance in point 8. This national declaration of performance is issued in accordance with the Act of 16 April 2004 on construction products, under the sole responsibility of the manufacturer.

On behalf of the manufacturer

Quality specialist  
Mirosław Pawłowski



Sarbinowo, 11 February 2025